

## Specification



Basic Parameters	US2000C	US3000C	Phantom-S
Nominal Voltage (V)	48	48	48
Nominal Capacity (Wh)	2400	3552	2400
Usable Capacity (Wh)	2280	3374.4	2200
Dimension (mm)	442*410*89	442*420*132	440*440*88.5
Weight (Kg)	24	32	24
Discharge Voltage (V)	44.5 ~ 53.5	44.5 ~ 53.5	44.5 ~ 53.5
Charge Voltage (V)	52.5 ~ 53.5	52.5 ~ 53.5	52.5 ~ 53.5
Charge / Discharge Current (A)	<b>25(Recommend)</b>	37 (Recommend)	25(Recommend)
	50 (Max@60s)	74 (Max@60s)	50 (Max@60s)
	90 (Peak@15s)	90 (Peak@15s)	100 (Peak@15s)
Communication Port	RS485, CAN	RS485, CAN	RS485, CAN
Single string quantity(pcs)	16	16	8
Working Temperature/°C	0~50	0~50	0~50
Shelf Temperature/°C	-20~60	-20~60	-20~60
Humidity	5%~95%	5%~95%	5%~95%
Altitude (m)	<2000	<2000	<2000
Design life	15 <sup>+</sup> Years (25°C/77°F)	15 <sup>+</sup> Years (25°C/77°F)	15 <sup>+</sup> Years (25°C/77°F)
Cycle Life	>6000, 25°C	>6000, 25°C	>6000, 25°C
Authentication Level	IEC62619/CE /UN38.3	VDE2510-50/IEC62619/UL1973 UL9540A/CE/UN38.3	IEC62619/CE /UN38.3
Feature	Pre-Charge Dual-active protection Flexible current steps Dry contact wake up	Pre-Charge Dual-active protection Flexible current steps Dry contact wake up	